



1		
2		5
3		6
4		8
5		11



RG-IIB-K75AS/K86AS	A	LED	
1080P	4K		
RG-IIB-K75AS/K86AS			
178			
RG-IIB-K75AS/K86AS			
RG-IIB-K75AS/K86AS	7H		AG
RG-IIB-K75AS/K86AS			
Touch			
HDMI			
RG-IIB-K75AS/K86AS	OPS		Windows
Andorid			
Android8.0	64		
	Android		
	Intel	OPS-C	CPU
OPS			
RG-IIB-K75AS/K86AS	OPS		
	Windows		

	RG-IIB-K75AS	RG-IIB-K86AS
	75	86
	16:9	16:9
	3840X2160	3840X2160
	450cd/	400 cd/
	60Hz	60Hz
	178°/178°	178°/178°
MTBF	≥200000	≥200000
	20	

VGA in×1

VGA in×1

PC-Aud

	100 V ~ 240 V/AC, 50/60 Hz	100 V ~ 240 V/AC, 50/60 Hz
OPS-C	400W	440W
	<=0.5W	<=0.5W
(W*D*H)	1741.7mmx103.4mmx1060.2mm	1995.2mmx111.9mmx1206.3mm
(W*H*D)	1880mmx280mmx1160mm	2140mmx280mmx1340mm
	59.1±1.5KG	76.6±1.5KG
	77.6KG±1.5KG	97.0KG 1.5KG



RG-IIB-K75AS	20	75	4K	20
		OPS		
RG-IIB-K86AS	20	86	4K	20
		OPS		
RG-BoardMate-H				
				®
RG-BoardMate-B				
RG-OPS-C-I3V1	Intel	OPS-C		® ™ i3

